# **CanProx Key Tag III**

FOR 125 kHz READERS







## **FEATURES**

- Smallest proximity key tags
- Ergonomic, and extremely durable
- Can be placed on a key ring for convenient entry
- Up to 3.5 inches (88 mm) read range
- Quick delivery



Cansec's CanProx Proximity Key Tags are small, ergonomic, and extremely durable, provide excellent read range. They are equipped with a eyelet for secure attachment to a key ring. They can be ordered to support certain HID® and AWID® 125 kHz proximity protocols.

## **CanProx Key Tag III**

## FOR 125 kHz READERS

### **SPECIFICATIONS**

| Technology             | Proximity   |
|------------------------|---|
| Frequency              | 125 kHz   |
| Operation              | Passive (no battery)  |
| Туре                   | Key Tag   |
| Formats                | Wiegand (26-bit and 37-bit formats)   |
| Technologies Supported | CA-CP3KT-A##: Certain AWID® 125 kHz proximity protocols supported CA-CP3KT-H##: Certain HID® 125 kHz proximity protocols supported  |
| Material               | ABS   |
| Color                  | Black and white   |
| Eyelet                 | Standard reinforced eyelet  |
| Marking <sup>1</sup>   | Fob: ID, Cansec web address<br>Issuing Certificate Card: Facility Code, ID, issue date and issued to  |
| Imaging                | N/A   |
| Read Range             | Up to 3.5 inches (88 mm)  |
| Warranty               | 1 year  |
| Dimensions             | Fob: $1.25''W \times 1.58''H \times 0.2''D$ [32 mm (W) $\times$ 40 mm (H) $\times$ 5 mm (D)]<br>Issuing Certificate Card: $2.1''W \times 3.4''H \times 0.031''D$<br>[53 mm (W) $\times$ 86 mm (H) $\times$ 0.79 mm (D)] |
| Weight                 | Fob: 0.14 oz (4 g), Issuing Certificate Card: 0.19 oz (5.5 g)   |
| Operating Temperature  | -35° F to 122° F (-37° C to +50° C)   |
| Humidity               | 0 - 95% non-condensing  |
|                        |   |

#### **NOTE:**

Specify Facility Code and ID Range for Hurricane or third party systems. For SmartLock systems, no Facility Code or ID Range required.

## PART NUMBERS

CA-CP3KT-A37 (Cansec 37-bit AWID® 125 kHz proximity protocol)

CA-CP3KT-A26 (26-bit AWID® 125 kHz proximity protocol)

CA-CP3KT-H37 (Cansec 37-bit HID® 125 kHz proximity protocol)

CA-CP3KT-H26 (26-bit HID® 125 kHz proximity protocol)

© 2010-2017 Cansec Systems Ltd. All rights reserved. Cansec®, CanProx®, and Cutting edge simplicity® are the registered trademarks of Cansec Systems Ltd. AWID is a registered trademark of Applied Wireless Identifications Group. HID, the HID logo, ProxCard, ISOProx, ProxKey, and MicroProx are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owner.

