


SPECIFICATIONS

LE-Series Door Stations

Surface and Flush Mount



COMMON SPECIFICATIONS:

System: LEM, LEF, LAF-C

Speaker: 20 ohms

Wiring Distance: 650' w/22AWG; 1600' w/18AWG

Temp. Rating: 14 to 140 F

LE-D Specifications:


Dimensions: 4-3/4" x 3-7/16" x 1-1/8"


Material: ABS plastic

Color: Black faceplate, white trim ring

LE-D FEATURES:

- · Weather resistant for outdoor use
- Push button to call master station(s)
- · Hands free communication when master answers
- · Compact surface mount design
- · Mounts to 1-gang box or ring





Common Specifications, plus: LE-DA Specifications:

Material: Plastic case,


stainless steel faceplate


Dimensions: 4-1/2" x 4-9/16" x 1-9/16"

LE-DA FEATURES:

- · Weather resistant for outdoor use
- Same calling and communication as LE-D
- Slim flush mount design
- Stainless steel faceplate
- · Mounts in 2-gang box or ring







Common Specifications, plus: LE-DL Specifications:

Backlight: 12V DC from system Material: Anodized aluminum Dimensions: 6-7/8" x 4-3/4" x 1"

LE-DL FEATURES:

- · Weather resistant for outdoor use
- Same calling and communication as LE-D
- · Directory strip with backlighting option
- · Slim surface mount design
- · Anodized aluminum cover
- Mounts to 1-gang box or ring

MOUNTING & INSTALLATION:

