

## LE-SS/A & LE-SSR

### Vandal and Weather Resistant Sub Station



#### DESCRIPTION:

The LE-SS/A and LE-SSR are vandal and weather resistant sub stations for Aiphone's LEM, LEF, and IX (with IX-1AS) systems. The units are constructed of 12 gauge stainless steel. They can be flush mounted into a standard 2-gang box or surface mounted into the SBX-2G/A. Each unit includes tamper proof screws and a tool for installation. The LE-SS/A has a stainless steel mechanical call button. The LE-SSR features a red mushroom type button. Communication at the sub station is hands-free.

#### FEATURES:

- Vandal and weather resistant
- Stainless steel mechanical call button (LE-SS/A)
- Red mushroom type call button (LE-SSR)
- Moisture and puncture resistant speaker
- 3-layer steel baffle protects speaker from tampering
- Hands-free communication when master answers
- Fits standard 2-gang electrical box

#### SPECIFICATIONS:

Power Source:	Supplied by master
Speaker:	20Ω, 2-1/2" diameter, water and puncture resistant
Call button:	Stainless steel SPST (LE-SS/A) Red mushroom SPST (LE-SSR)
Faceplate:	12 gauge stainless steel
Communication:	Hands-free
Mounting:	Flush mount into a 2-gang box or surface mount with SBX-2G/A
Mounting hardware:	6x32 T-10 Torx tamper screws (tool supplied)
Terminations:	Color-coded prewired pigtails
Wiring:	2 conductor shielded with LEM and IX systems. Aiphone wire 822202 or 821802 3 conductor shielded with LEF system. Aiphone wire 822203 or 821803
Wiring distance:	650' w/22AWG, 1600' w/18AWG
Dimensions:	4-11/16" H x 4-11/16" W x 2" D