



PRODUCT FEATURES

- Can be field cut to accommodate non-standard openings up to 48"
- Activates a DPST 2 Amp rated relay when touched (no mechanical movement) which will allow free egress, or initiates the delay on an exit delay timer
- Backup push button
- 16 ft. [4.8m] 22AWG 6 conductor cable and armored door cord included
- Automatic dual voltage 12VDC/24VDC
- Available ElectroLynx® ready
- MagnaCare Lifetime Replacement No Fault Warranty

PRODUCT OPTIONS

- 36" Length
- 42" Length
- 48" Length
- EL- Prefix any model for ElectroLynx® ready
- D- Prefix any model for dummy bar with no release function

- Through-bolt kit works on doors up to 2-1/4" thick
- Cover plates for retrofit of competitor products
- Trailing edge timer

SPECIFICATIONS


- ANSI/UL 294 Listed
- CSA-C22.2 No.205 Listed
- CSFM – California State Fire Marshal Approved
- MEA- City of New York Approved
- CE: EN 50091-1, EN 61000-6-2 Approved

Electrical:
40mA at rest; 25mA releasing at 12VDC or 24VDC

Operating Temperature:
+32 to +110F [0 to +43C]
Recommended for indoor use

Shipping Weight:
7lbs [3.18kg] to 9lbs [4.08kg]
depending on length

Finishes:
BK - Black anodized
CL - Clear anodized



TCP covers unwanted mounting holes from previously installed exit bars



TSB

Touch Sense Bar

Touch-Triggered Release for Reliable Egress

The TSB Touch Sense Bar provides touch-triggered release of magnetically locked, non-fire-rated doors. Touching the bar, even through light gloves or clothing, triggers an electronic sensor that releases the lock. For indoor use only, the TSB installs easily on all types of metal, aluminum or wood frame doors. Meets "no special tools or knowledge" criteria in code requirements.

MODELS

PART # | Description

TSB-BK	TSB - 36", Black Anodized
TSB-BK-42	TSB - 42", Black Anodized
TSB-BK-48	TSB - 48", Black Anodized
TSB-BKT	TSB - 36" w/ Trailing Edge Timer [3 sec], Black Anodized
TSB-BKT-48	TSB - 48" w/ Trailing Edge Timer [3 sec], Black Anodized
TSB-CL	TSB - 36", Clear Anodized
TSB-CL-42	TSB - 42", Clear Anodized
TSB-CL-48	TSB - 48", Clear Anodized
TSB-CLT	TSB - 36" w/ Trailing Edge Timer [3 sec], Clear Anodized
TSB-CLT-42	TSB - 42" w/ Trailing Edge Timer [3 sec], - Clear Anodized
DTSB-BK	Dummy TSB Bar - 36" w/ End Caps & Fasteners, Black Anodized
DTSB-BK-42	Dummy TSB Bar - 42" w/ End Caps & Fasteners, Black Anodized
DTSB-BK-48	Dummy TSB Bar - 48" w/ End Caps & Fasteners, Black Anodized
DTSB-CL	Dummy TSB Bar - 36" w/ End Caps & Fasteners, Clear Anodized
DTSB-CL-42	Dummy TSB Bar - 42" w/ End Caps & Fasteners, Clear Anodized
DTSB-CL-48	Dummy TSB Bar - 48" w/ End Caps & Fasteners, Clear Anodized
EL-TSB-BK	TSB - 36", Black Anodized, ElectroLynx
EL-TSB-BK-42	TSB - 42", Black Anodized, ElectroLynx
EL-TSB-BK-48	TSB - 48", Black Anodized, ElectroLynx
EL-TSB-CL	TSB - 36", Clear Anodized, ElectroLynx
EL-TSB-CL-42	TSB - 42", Clear Anodized, ElectroLynx
EL-TSB-CL-48	TSB - 48", Clear Anodized, ElectroLynx
TCP-BK	Touch Bar Cover Plates - Set of 2, Black Anodized
TCP-CL	Touch Bar Cover Plates - Set of 2, Clear Anodized
TSB-TDM	Through Door Mounting Kit for TSB-3



DUAL VOLTAGE

SECURITRON
ASSA ABLOY