

IR-29 Indoor Motion Detector

Enhanced Flexibility and Affordability



- Two Battery Selections
- Fast Speed Signal Transmission
- Microprocessor Controlled
- Advanced ADSP Algorithms

IR-29 Series is a microprocessor controlled PIR Motion Detector that offers quality detection. The advanced Adaptive Digital Signal Processing (ADSP) algorithms in IR-29 Series guarantee high performance in sensitivity, reliability, and false alarm immunity. The sensitivity levels of IR-29 Series can be adjusted to suit different premises. To further enhance its flexibility and affordability, Lithium or Alkaline batteries are available for selection.

IR-29-F1 and IR-29-F2 adopt the latest RF technologies to deliver super speed signal transmission and extensive communication range up to 300 meters in open space. With fast data transmission, IR-29-F1 and IR-29-F2 are designed to effectively reduce signal collisions and further extend battery life. IR-29-F1 is compatible with AC powered F1 control panels and IR-29-F2 is compatible with battery operated F2 control panels

Easy and flexible to install, IR-29 Series sends regular supervision signals to check system integrity and has tamper-proof design to prevent the opening or removal of its housing. The compact, low-profile housing allows IR-29 Series to blend naturally with the settings where it is installed.

Features

- Powered by pre-inserted Lithium or Alkaline batteries
- Microprocessor controlled with advanced ADSP algorithms for false alarm immunity
- Long battery life
- Super speed signal transmission (F1 and F2 models only)
- Compatibility with AC powered F1 panels (F1 model only)
- Compatibility with battery operated F2 panels (F2 model only)
- Two selectable sensitivity levels
- Surface or corner mount with tamper protection against removal
- Randomized supervision signals for system integrity checks and troubleshooting
- Low battery detection
- Superior white light and noise rejection
- Superior radio interference rejection of up to 20V/m at frequencies of 100KHz to 1GHz
- Detection range: 12 meters over a 110° angle
- Automatic power saving mechanism
- Insect and dirt proof
- Compact and low-profile
- LED serving as a fault and test mode indicator or a walk test mode button
- Temperature compensated sensitivity control
- Compliant with CE and FCC requirements
- Certified to Standard: EN 50131 Grade2, Class II

IR-29 PIR Motion Detector Series

Specifications

| | IR-29 | IR-29-F1 | IR-29-F2 |
|-------------------------|--|---|---|
| Battery Available | 1.5V AA Alkaline Battery X 2 (pre-inserted) | 1.5V AA Alkaline Battery X 2 (pre-inserted) | 1.5V AA Alkaline Battery X 2 (pre-inserted) |
| Battery Life (Alkaline) | CR123A 3V 1500mAh x1 (pre-inserted) 5.9* years (433MHz) 5.2* years (868.35MHz) 4.2* years (868.6375MHz) | CR123A 3V 1500mAh x1 (pre-inserted) 5.5* years (433MHz) 5.44* years (868.6375MHz) | CR123A 3V 1500mAh x1 (pre-inserted) 4.8* years |
| Battery Life (Lithium) | 5.9* years (433MHz) 5.1* years (868.35MHz) 4.1* years (868.6375MHz) | 5.8* years (433MHz) 5.44* years (868.6375MHz) | 5* years |
| Frequency Available | 433MHz/ 868.35MHz/ 868.6375MHz | 433MHz/ 868.6375MHz | 433MHz |
| Operating Temperature | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C |
| Operating Humidity | Up to 85% non-condensing | Up to 85% non-condensing | Up to 85% non-condensing |
| Dimensions | 53.2mm X 67mm X 89.2mm | 53.2mm X 67mm X 89.2mm | 53.2mm X 67mm X 89.2mm |

* Note: Battery life varies based on environment and usage.



Consolidated
**SECURITY
MERCHANTS**



1300 663 904

VIC: Melbourne
Unit 144, Axxess Corporate Park,
45 Gilby Road, Mt Waverley
Melbourne, VIC 3149
PH: 03 9558 8455

NSW: Sydney
Unit 4, 60 Roberts Road,
Greenacre,
NSW 2190
Tel:02 9890 5300

QLD: Brisbane
Unit 1, 107 Da Vinci Business Park
2-6 Leonardo Drive, Brisbane Airport
Eagle Farm, QLD 4007
Tel:07 3552 5966

WA: Perth
Unit 4, 103 Erindale Road,
Balcatta, WA, 6021
Tel:08 9344 2555

SA: Adelaide
Unit 1, 60 Grove Avenue,
Marleston, SA 5033
Tel: 08 8297 5555

TAS: Local Electronics
194A Main Road Moonah,
Tas 7009
Tel: 03 62727288