

# IRD-23 Ceiling Mount 360 Detector

## 360° Look-Down Capability Eliminates Blind Spots and Undetected Intrusion



- 360° look-down view
- Covers an area up to 26' (8 m) in diameter
- Ideal for passages and entrances
- Minimizes tampering and vandalism

The IRD-23 is a ceiling mount PIR motion sensor with a 360° look-down capability to eliminate blind spots in the monitored area. When mounted on a ceiling at 8.8' to 13' (2.7 m to 4 m) high, the IRD-23 has a 360° look-down view that covers an area of 20' to 26' (6 m to 8 m) in diameter. The IRD-23 is an ideal solution for the protection of doorways, corridors, hallways and passages, where a moving person cannot evade passing through the detector's coverage pattern.

Mounting the IRD-23 on the ceiling effectively deters tampering and vandalism, thereby making the detector also a best choice for the safeguarding of entrances to public or larger spaces such as lobbies, retail stores, galleries or offices. This application of the IRD-23 will place any person moving through the monitored entrance in the direct field of view of the detector, leaving no chance for an intruder to escape detection.

The discreet housing of the IRD-23 attracts minimal visual attention and protects the detector from being recognized as a security device. This microprocessor-controlled detector further adopts advanced Adaptive Digital Signal Processing (ADSP) algorithms to enhance false alarm immunity.

### Features

- 360° look-down capability eliminates blind spots
- Up to 26' (8m) diameter coverage pattern
- Mounted on the ceiling to minimize tampering and vandalism
- Discreet housing attracts minimal visual attention and protects the detector from being recognized as a security device
- Twist-off cover for easy installation
- Ideal for the protection of doorways, corridors, hallways and passages
- Suitable also for the monitoring of entrances to larger spaces such as offices, lobbies, galleries or retail stores
- Microprocessor controlled with advanced Adaptive Digital Signal Processing (ADSP) algorithms for false alarm immunity
- Two selectable sensitivity levels
- Low battery detection
- Automatic power saving mechanism
- Protected against tampering and sabotage
- Regular supervisory signals ensure device integrity
- Walk-test LED also serves as a fault indicator
- Compliant with CE and FCC requirements

### Specifications

Power	CR123A 3V lithium battery x 1
Battery life	To be confirmed
Standby current drain	30uA at 3 to 3.6 VDC
Available radio frequencies	433MHz/868.35MHz FM/868.6375MHz Narrow FM
Radio frequency ranges	433MHz or 868.35MHz FM: Over 200 meters in open space 868.6375MHz Narrow FM: Over 300 meters in open space
Operating temperature	-10°C to +45°C
Operating humidity	Up to 85% non-condensing
Dimensions	Ø 106 mm x 30.35 mm
Mounting height	8.8' to 13' (2.7 m to 4 m)



Consolidated  
**SECURITY  
MERCHANTS**



**1300 663 904**

**VIC: Melbourne**  
Unit 144, Axxess Corporate Park,  
45 Gilby Road, Mt Waverley  
Melbourne, VIC 3149  
PH: 03 9558 8455

**NSW: Sydney**  
Unit 4, 60 Roberts Road,  
Greenacre,  
NSW 2190  
Tel:02 9890 5300

**QLD: Brisbane**  
Unit 1, 107 Da Vinci Business Park  
2-6 Leonardo Drive, Brisbane Airport  
Eagle Farm, QLD 4007  
Tel:07 3552 5966

**WA: Perth**  
Unit 4, 103 Erindale Road,  
Balcatta, WA, 6021  
Tel:08 9344 2555

**SA: Adelaide**  
Unit 1, 60 Grove Avenue,  
Marleston, SA 5033  
Tel: 08 8297 5555

**TAS: Local Electronics**  
194A Main Road Moonah,  
Tas 7009  
Tel: 03 62727288