

# SD-29 Series Multi-functional Smoke Detector

## **Protecting What Matters Most**



- · Multi-functional Smoke/Heat Detector
- Built-in PIR Motion Sensor (optional)
- Built-in Heat Detector (optional)
- Built-in Emergency Light (optional)

Multi-functional wireless smart smoke detector with powerful functions, the SD-29 series is designed to protect your family against potential fire hazards, and build a more comfortable lifestyle. This series was crafted from the belief that sensor should have multiple functions and abilities, thus a unique feature of SD-29 is the optional rate-of-rise heat detection and built-in PIR motion sensor, and/or emergency light. With its small and streamlined design, it will be a seamless addition to your home décor and give you a peace of mind.

SD-29 delivers optimal performance in in detecting fire and rate-of-rise heat detection. Moreover, SD-29 optional built-in PIR motion sensor detects movements to create custom scenes to light up the hallway in the middle of the night or help users save energy. The SD-29 optional built-in emergency light can further provide visual alarm alerts and notifications.

SD-29 utilizes the latest reflective photoelectric sensor and advanced microprocessor to deliver optimum performance in detecting fire and rate-of-rise heat detection. When it comes to safety, there is no room for compromise.

#### Features

- Reflective photoelectric sensor to detect smoke from any source, especially smoldering fires
- Rate-of-rise heat detection when temperature exceeds
   57.25°C or rises by 8.25°C per minute (optional)
- Auto-calibration every month to re-adjust detection threshold value
- Self-diagnostics function to ensure optimal performance
- · Loud 85dB Siren for audio alert
- · Wireless for easy and flexible installation
- Randomized supervision signals to check system integrity

- Built-in PIR motion detects movements and supports scene creation (optional)
- Built-in Emergency light to provide visual alerts (optional)
- · Alarm silence button to guiet nuisance alarms
- Excellent stability with high sensitivity
- Extensive RF range and fast speed data transmission
- · LED status indicators for visual notification
- · Low battery detection
- · Suitable for residential and commercial premises



### SD-29 Multi-Functional Smoke Detector Series

## Specifications

#### SD-29-HME-F1

433 MHz / 868MHz	
3V, AA Alkaline battery x 2 / 3V, CR123 Lithium battery x 3	
8 years* (Alkaline) / 10 years* (CR123)	
85dBA at 3m	
±1°C	
Up to a radius of 8 meters (at 3 meter mounting height**)  (SD-29-M / SD-29-HM / SD-29-HME only)	
-10°C to 45°C (14°F to 113°F)	
Up to 85% non-condensing	
105mm x 105mm x 41mm	
	3V, AA Alkaline battery x 2 / 3V, CR123 Lithium battery x 3  8 years* (Alkaline) / 10 years* (CR123)  85dBA at 3m  ±1°C  Up to a radius of 8 meters (at 3 meter mounting height**)  (SD-29-M / SD-29-HM / SD-29-HME only)  -10°C to 45°C (14°F to 113°F)  Up to 85% non-condensing

#### SD-29-HME-SC-AC-F1

RF Frequencies	433 MHz / 868 MHz
Power Source	100-240AC, 50/60Hz
Backup Battery	200mAh, NiMh battery pack
Battery Battery Life	39 days*
Audible Output	85dBA at 3m
Temperature Sensitivity	±1"C
PIR Motion Detection Range	Up to a radius of 8 meters (at 3 meter mounting height**)  (SD-29-M-SC-AC / SD-29-HM-SC-AC / SD-29-HME-SC-AC only)
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	105mm x 105mm x 41mm

<sup>\*</sup>Note: Actual battery life may vary with product settings, operating environment, and usage.

## Ordering Information

SD-29-H-F1	Battery-powered Smoke Detector with Heat Detector
SD-29-M-F1	Battery-powered Smoke Detector with PIR Motion Sensor
SD-29-HM-F1	Battery-powered Smoke Detector with Heat Detector and PIR Motion Sensor
SD-29-HME-F1	Battery-powered Smoke Detector with Heat Detector, PIR Motion Sensor and Emergency Light
SD-29-H-SC-AC-F1	AC-powered Smoke Detector with Heat Detector and Interconnection function
SD-29-M-SC-AC-F1	AC-powered Smoke Detector with PIR Motion Sensor and Interconnection function
SD-29-HM-SC-AC-F1	AC-powered Smoke Detector with Heat Detector, PIR Motion Sensor and Interconnection function
SD-29-HME-SC-AC-F1	AC-powered Smoke Detector with Heat Detector, PIR Motion Sensor and Emergency Light and

Interconnection function





1300 663 904

<sup>\*\*</sup>Note: Mounting above 3 meters may affect detection performance.